



# Tecsom Décostructure "Tip Sheared"

TecSOM

## Specifications

DESCRIPTION	NORM	DATA
Composition fibreuse / Pile Fibre		100% Polyamide (Teint masse/Solution dyed)
Aspect de surface / surface aspect		Structuré bouclé&rasé / Multi Level Cut&Loop
Jauge / Gauge		5/64e loop pile
Densité / Tuft Density	ISO 1763	223 600 Stitches/m <sup>2</sup>
Poids de fil / Total pile mass	ISO 8543	885 g/m <sup>2</sup>
Masse de velours utile / Mass of pile above the substrate	ISO 8543	500 g/m <sup>2</sup>
Epaisseur velours utile / Thickness of pile above the substrate	ISO 1766	4 mm
Densité du velours de surface / Surface pile density	ISO 8543	0,125 g/cm <sup>3</sup>
Masse totale / Total Weight	ISO 8543	4835 g/m <sup>2</sup>
Epaisseur totale / Total Thickness	ISO 1765	7,7 mm
Premier dossier / Primary Backing		Non tissé / Non woven primary backing
Envers / Backing		Matières recyclées renforcées par un voile de verre Vinyl backing reinforced with glass fiber (100 % recycled PVC)
Dimensions / Tile Size		50x50cm
Dalles par boîte / Tiles per Box		20 = 5m <sup>2</sup>
Sens de pose / Installation		

## Technical performances











Classification EN 1307 - 33 / Commercial Heavy  
Luxury Class - LC2



Feu / Fire rating EN 13501-1 : BflS1

RHO - LRV	
10 couleurs / 10 colors	%
Patio - 135160505-00XXX	
042	
035	9,0%
166	
024	7,0%
144	5,6%
Prism - 135100505-00XXX	
179	
049	
169	
029	
039	

<b>Heated Floor</b>  ISO 10456 0,10 m <sup>2</sup> K/W	<b>Impact noise reduction</b>  EN ISO 10143-3 $\Delta L_{(w)}$ 25 dB
<b>Electrostatic prop.</b>  ISO 6356 $\leq 2,0kV$ ISO 10965 $RT \approx 10^{10}\Omega$	<b>Sound absorption</b>  ISO 11654 $\alpha_w = 0,20 (H)$
<b>Dimensional Stability</b>  EN 986 $\leq 0,10\%$	<b>Colour Fastness</b>  EN 105 - B02 7/8
 N° 0679-CPR-0196 07 EN 14041 : 2004	<b>Castor Chair</b>  EN 985 Passed $R_{\geq 2,4}$

## Environmental issues

LEED

Répond à la démarche  
HQE



